




DIN 70mm

Features :

- Monitors Electrical Parameters for 4 loads (3Ø), 12 loads (1Ø)
- RS485 Communication MODBUS RTU Protocol
- Self Powered
- Power (Active, Reactive, Apparent)
- Energy (Active, Reactive, Apparent)

Certification : 

Display Specifications

Display	LCD with Backlight
Digits	1 row of 4 digits, 2 rows of 7digits
LED Indications	Integration of Energy

Input Specifications

Electrical Connection	3Ø - 4 wire, 1Ø - 2 wire
Input Voltage Range	60V to 300V AC (L - N) 104V to 520V AC (L - L)
Frequency	45 to 65Hz
Display Scrolling	Automatic / Manual
Power Consumption	8VA max
Display Reset	Programmable (For energy)
Resolution	For energy : 0.01k, 0.1k, 1k, 0.01M, 0.1M, 1M (depending upon CT ratio x PT ratio) For Power, Voltage : Auto Resolution For Power Factor : 0.01 Voltage (L - L / L - N) : $\pm 0.05\%$ of F.S. Current : $\pm 0.05\%$ of F.S. Power Factor : ± 0.01 Frequency : $\pm 0.1\%$ Power (Active, Reactive, Apparent) : 1% Energy (Active, Reactive, Apparent) : 1%
Memory Retention	10 years (For energy)
Measuring Parameters	Voltage (L - L / L - N) (Individual / Average) of 4 Channels, Current (Individual / Average) of 4 Channels, Power (Active, Reactive & Apparent) (Individual) of 4 Channels, Power factor & Frequency of 4 Channels, Energy (Active, Reactive & Apparent) (Individual / Total) of 4 Channels

Output Specifications

Communication, Interface and Protocol	RS485 and MODBUS RTU
Communication Address	1 to 255
Transmission Mode	Half duplex
Transmission Distance	500 meter maximum
Transmission Speed	300, 600, 1200, 2400, 4800, 9600, 19200 (in bps)
Parity	None, Odd, Even
Stop Bits	1 or 2
Response Time	100ms (max and independent of baud rate)

Auxiliary Supply Specifications

Supply Voltage	60 to 300V AC, 50 / 60Hz, Self - Supplied (V1, N)
----------------	---

Settable Parameters

CT Primary	1A to 10kA (Programmable for any value)
CT Secondary	330mV
PT Primary	100 to 10kV (Programmable for any value)
PT Secondary	100V to 500V AC (L - L) (Programmable for any value)


Environmental Specifications

Temperature	Operating Temperature : -10° to 55°C Storage Temperature : -20° to 75°C
Humidity (non - condensing)	Upto 85% RH


Mechanical Specifications

Mounting	Din Rail
Weight	290gms


Dimensions



Side View



Terminal Connection



Compliance

Applicable EMI / EMC Standards

Product Standard : IEC 61326 - 1

Category		Standards Compliance
ESD Immunity	IEC 61000 - 4 - 2	Level IV (Air discharge : 15kV), (Contact Discharge : -8kV)
Surge Immunity	IEC 61000 - 4 - 5	+ / - 4kV common mode, (Line to Ground)
Radiated Susceptibility	IEC 61000 - 4 - 3	Level III, 80 to 1000MHz (10V / m) Level II, 1.4GHz to 2GHz (3V / m) Level I, 2GHz to 2.7GHz (1V / m)
Conducted Susceptibility	IEC 61000 - 4 - 6	Level II (3V / m)
Voltage Dips and Interruptions	IEC 61000 - 4 - 11	Dips : 0% residual voltage / 1 cycle (Criteria B), 40% residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Criteria C) 70% residual voltage / 25 cycles 50Hz / 30 cycles 60Hz (Criteria C) Interruptions : 0% residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Criteria C)
Conducted Emission	CISPR - 11	
Radiated Emission	CISPR - 11	
Electrical Fast Transient	IEC 61000 - 4 - 4	Level IV (4kV)

Ordering Information

Product Code	Supply Voltage	Output	Certification
MRJ4M-QUAD	Self Supplied (V1, N) 60 to 300V AC	Comm. (RS485)	CE