

# green light block for head Ø22 integral LED 230...240V plug-in connector

ZBVM34

! Discontinued on: 15 Jun 2023

① Discontinued

## Main

Range of product	Harmony XB4 Harmony XB5	
Product or component type	Light block	
Device short name	ZBV	
Sale per indivisible quantity	5	
Connections - terminals	Plug-in connector	
Signalling type	Steady	
Light source	Protected LED	
Bulb base	Integral LED	
Light block supply	Direct	
Light source colour	Green	
[Us] rated supply voltage	230240 V AC at 50/60 Hz	

# Complementary

Net weight	0.016 kg	
Supply voltage limits	195264 V AC	
Current consumption	14 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1	
Electrical composition code	M2 M3 M4 M5 M6 M10 MF1	

#### **Environment**

Protective treatment	тн
Ambient air temperature for storage	-4070 °C
Ambient air temperature for	-4070 °C

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

IP degree of protection	IP20 conforming to IEC 60529	
Standards	EN/IEC 60947-1	
	EN/IEC 60947-5-4	
	JIS C8201-5-1	
	EN/IEC 60947-5-1	
	CSA C22.2 No 14	
	UL 508	
	EN/IEC 60947-5-5	
	JIS C8201-1	
Resistance to fast transients	2 kV conforming to IEC 61000-4-4	
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3	
Resistance to electrostatic	6 kV on contact (on metal parts) conforming to IEC 61000-4-2	
discharge	8 kV in free air (in insulating parts) conforming to IEC 61000-4-2	
Electromagnetic emission	Class B conforming to IEC 55011	
[Us] rated supply voltage	230240 V	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.7 cm
Package 1 Width	4.4 cm
Package 1 Length	5.3 cm
Package 1 Weight	8 g
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Height	5.7 cm
Package 2 Width	4.4 cm
Package 2 Length	5.3 cm
Package 2 Weight	43 g
Unit Type of Package 3	S02
Number of Units in Package 3	200
Package 3 Height	15 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	2.175 kg

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)

## **Use Again**


○ Repack and remanufacture	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

# ZBVM34


# **Dimensions Drawings**

#### **Dimensions**

## with ZB5AZ009 Fixing Collar



## with ZB4BZ009 Fixing Collar



# **Technical Illustration**

# **Dimensions**

