




5 mm		6,5 mm		6,5 mm	
M5 x 0,5 fine thread sturdy housing		short and robust steel housing high switching frequency		robust steel housing high switching frequency	
0,8 mm ●	0,8 mm ●	2 mm ●	2 mm ●	2 mm ●	2 mm ●
					
IFR 05.26.35/L	IFRM 05P1501/S35L	IFRM 06P1713/L	IFRM 06P1703/S35L	IFRM 06P1701/L	IFRM 06P1701/S35L
IFR 05.26.45/L	IFRM 05P3501/S35L	IFRM 06P3713/L	IFRM 06P3703/S35L	IFRM 06P3701/L	IFRM 06P3701/S35L
IFR 05.26.15/L	IFRM 05N1501/S35L	IFRM 06N1713/L	IFRM 06N1703/S35L	IFRM 06N1701/L	IFRM 06N1701/S35L
IFR 05.26.25/L	IFRM 05N3501/S35L	IFRM 06N3713/L	IFRM 06N3703/S35L	IFRM 06N3701/L	IFRM 06N3701/S35L
10 - 30 VDC		10 - 30 VDC		10 - 30 VDC	
< 18 mA		< 18 mA		< 18 mA	
100 mA		200 mA		200 mA	
< 2,5 V		< 3 V		< 3 V	
5 kHz		5 kHz		5 kHz	
0,8 mm		2 mm		2 mm	
3...20 %		3...25 %		3...25 %	
red LED	4 quadrant LED red	red LED	4 quadrant LED red	red LED	4 quadrant LED red
yes	yes	yes	yes	yes	yes
yes	yes	yes	yes	yes	yes
-25...+75 °C		-25...+75 °C		-25...+75 °C	
stainless steel (1.4305)		stainless steel (1.4305)		stainless steel (1.4305)	
PBT		PBT		PBT	
IP 67		IP 67		IP 67	
ESW 31, ESG 32		ESW 31, ESG 32		ESW 31, ESG 32	
		support 109474 for details see accessories section		support 109474 for details see accessories section	
